



# Model HV-100-25 HV-100-25E ANGLE HOSE VALVE



- Sensitive and Accurate Performance
- UL/ ULC Listed
- FM Approved

The Cla-Val 2 1/2" Model HV-100-25 features a Forged Brass finish body with Forgeline Bonnet and Seat Assembly.

A brass body is standard but can be supplied with a polished chrome, cast chrome or polished brass finish.

**Available hose threads include:** BCT, CSA, NSST, NPSH, NST, QST, WCT, Louisville, Cleveland, Chicago, Pittsburg, New Cincinnati, New York Corp, New York Fire Department, Richmond, and Raleigh



## Specifications

Cla-Val Model HV-100-25 UL/ULC Listed and FM Approved 300 lb. (2070 kPa) pressure tested standard angle hose valve where standpipe pressure on a hose rack assembly or as a fire department outlet connection is less than 90 psi (620 kPa).

## Standards

**NFPA 14**  
• Class II & III Standpipe Systems

### End Connection Options

1. Female NPT x Male Hose (Angle) - FM
2. Female NPT x Female NPT
3. Groove X Male Outlet

Dimensions	End Connection Type		
	1	2	3
A	5" 127 mm	5" 127 mm	5" 127 mm
B (Open)	11" 279.4 mm	11" 279.4 mm	11-7/8" 301.6 mm
B (Closed)	9-3/8" 238.1 mm	9-3/8" 238.1 mm	9-3/8" 238.1 mm
C	3-1/4" 82.5 mm	3-1/4" 82.5 mm	3-1/4" 82.5 mm

## Dimensions

